

# 1 OVERVIEW



- 1. Outer Barrel
- 2. Hop-Up
- 3. Body
- 4. Bi-pod
- 5. Magazine
- 6. Jam Rod
- 7. Speed Loader
- 8. Suppressor Adapter
- 9. Assembly Tools
- 10. Sling

# 2 ASSEMBLY



Align the front clip correctly with the body.



Position the outer barrel towards the front first to ensure proper installation.



With outer barrel positioned correctly at the front, press down by the trigger assembly to seat it.



Locate the fasteners. The first screw is at the trigger guard. Note: Screw is preinstalled in body.



The second screw is located behind the magazine's well. Note: Screw is preinstalled in body.



Tighten both screws down using the supplied tools and in a clockwise direction.

### 3 BI-POD INSTALLATION



Loosen bi-pod clamp by turning the screw counterclockwise.



Position bi-pod on to front rail and tighten clamp by turning clockwise.



Press down firmly on top of locking button to extended bi-pod legs.

### 4 HOP-UP



Hop-up adjustment is located at the front of the magazine release.



Turn clockwise to increase hop-up and counterclockwise to decrease.

### 5 SAFETY



Move slider backwards to engage safety.



When ready to fire, move slider forwards to disengage safety.

### 6 BOLT OPERATION



1. Pull bolt upwards.  
2. Pull bolt all the way back.



1. Push bolt forward.  
2. Lock bolt back into place.

### 7 LOADING AND MAGAZINE REMOVAL



Install adapter to the included speed loader.



Press down on magazine. Position speed loader onto magazine as shown.



Once BBs are loaded, install the magazine.

Continued on next page

Continued from pg 2



Press down firmly until magazine clicks into place.



Locate magazine release button and press downwards to release. Prepare to grab it.



The magazine will eject. Pull back to remove.

## 8 SUPPRESSOR ADAPTER



Remove the barrel cap by turning counterclockwise.



Install suppressor adapter by turning clockwise.



Tighten adapter firmly until completely seated.

## 9 CHEEK REST



Locate and loosen the two screws by turning counterclockwise.



Pull up and position cheek rest to preferred setting.



Tighten the two screws by turning clockwise.